


CHERRY TC 1200



Models may vary from the image shown

Durable, reliable and practical - Class 1 terminal for contactless smart cards

CHERRY TC 1200 - the reliable solution for bidirectional communication with contactless chip cards. Design: intelligent. Operation: with one hand. Workmanship: high-quality.

Key benefits

- Class 1 smart card terminal
- Bidirectional communication for contactless smart cards
- LED status display
- High-quality workmanship, state-of-the-art technology and intelligent design
- One-handed operation and rubber surfaces to prevent slipping
- Attachable card clip to fasten contactless smart cards
- Connection via USB 2.0 port
- 1.75 m cable length for maximum freedom of movement
- Software supports Microsoft Windows, Linux and Mac OS X operating systems
- Supported standards: PC/SC, CCID, CT-API

Technical Data:

Housing colour:

Product dependant, see table "Models"

Weight (product):

approx. 75 g

Total weight (with packaging):

Product dependant, see table "Models"

Cable Length:

approx. 1.75 m

Storage Temperature:

-20°C to 65°C

Operating Temperature:

0°C to 50°C

Current Consumption:

max. 230 mA

Interface:

- USB

Product approvals:

- VDE GS 
- c-tick 
- UL 
- CE 
- FCC 

System requirements:

- USB connection

Dimensions (product):

76 x 62 x 11 mm

Packaging dimensions:

Product dependant, see table "Models"

Packaging (version):

Product dependant, see table "Models"

Smart card reader:

- Type: Contact-free
- Hardware interface: USB
- Chip-card protocols: T=CL
- Contact: contact-free reader in accordance with ISO14443A, ISO14443B, ISO15693
- Software interface: CT-API, PC/SC
- Compatible chip card types: MIFARE®, DESFire®, iCLASS®, ...
- Transmission speed reader <==> card: max. 848 kBit/s | 26 kbit/s (ISO15693)
- Transmission speed reader <==> system: max. 12 MBit/s

Packaging Unit:

- Number of products in the master package: Product dependant, see table "Models"
- Number of master packages per pallet: Product dependant, see table "Models"

Warranty:

2 years

Errors, technical changes and delivery possibilities excepted. Technical information refers only to the specifications of the products. Features may differ from the information provided.

Models:

	Product name	Order number	Housing colour	Total weight (with packaging)	Packaging dimensions	Packaging (version)	Number of products in the master package	Number of master packages per pallet
1	CHERRY TC 1200	JT-0200AB-0	pale grey	-	-	Collective packaging	90	24
2	CHERRY TC 1200	JT-0200AB-2	black	-	-	Collective packaging	90	24
3	CHERRY TC 1200	JT-0200WB-0	pale grey	approx. 96 g	110 x 40 x 70 mm	White box	150	20
4	CHERRY TC 1200	JT-0200WB-2	black	approx. 96 g	110 x 40 x 70 mm	White box	150	20